

## Customer Information

Date : .....

Company Name : .....

Engineer Name : .....

Program Name : .....

Required date : .....

### Example



Connectors	1		2		Material	Plating		Number of channel	
TVOP	<input type="checkbox"/>	<input type="checkbox"/>							
STARTOP	<input type="checkbox"/>	<input type="checkbox"/>							
38999 + LUXBEAM	<input type="checkbox"/>	<input type="checkbox"/>			Aluminium	<input type="checkbox"/>	<input type="checkbox"/>	Olive drab cadmium	<input type="checkbox"/>
EN4869					Inox	<input type="checkbox"/>	<input type="checkbox"/>	Nickel chimique	<input type="checkbox"/>
TACBEAM	<input type="checkbox"/>	<input type="checkbox"/>			Bronze	<input type="checkbox"/>	<input type="checkbox"/>	Black zinc nickel	<input type="checkbox"/>
ARINC 801	<input type="checkbox"/>	<input type="checkbox"/>							
CTOS	<input type="checkbox"/>	<input type="checkbox"/>							
CTOL	<input type="checkbox"/>	<input type="checkbox"/>							
MPO FIELD	<input type="checkbox"/>	<input type="checkbox"/>							
LC FIELD	<input type="checkbox"/>	<input type="checkbox"/>							
ST2		<input type="checkbox"/>							
FC		<input type="checkbox"/>							
SC		<input type="checkbox"/>							
LC		<input type="checkbox"/>							
MPO		<input type="checkbox"/>							
MT		<input type="checkbox"/>							

  

Shell type		Backshell		Dust cap	
	1	2		1	2
Reduced flange jam nut receptacle	<input type="checkbox"/>	<input type="checkbox"/>	Straight metallic	<input type="checkbox"/>	<input type="checkbox"/>
Jam nut receptacle	<input type="checkbox"/>	<input type="checkbox"/>	Straight Heatshrinkable	<input type="checkbox"/>	<input type="checkbox"/>
Square flange receptacle	<input type="checkbox"/>	<input type="checkbox"/>	Right angle Heatshrinkable	<input type="checkbox"/>	<input type="checkbox"/>
Plug	<input type="checkbox"/>	<input type="checkbox"/>	For pigtails	<input type="checkbox"/>	<input type="checkbox"/>

  

Application & Environmental Parameters	
Ground Military	<input type="checkbox"/>
Ground Vehicles	<input type="checkbox"/>
Avionics	<input type="checkbox"/>
Telecom / Laboratory	<input type="checkbox"/>
Operating temperature : .....	
Storage temperature : .....	
Other Parameters : .....	

Optical Wavelength (nm)	Fiber Optic	Performance	Cable definition
850 <input type="checkbox"/> 1310 <input type="checkbox"/>	Singlemode 9/125 <input type="checkbox"/> 50/125 OM4 <input type="checkbox"/>	Insertion loss : .....	Simplex <input type="checkbox"/> Duplex <input type="checkbox"/>
1300 <input type="checkbox"/> 1550 <input type="checkbox"/>	50/125 OM2 <input type="checkbox"/> 62,5/125 OM1 <input type="checkbox"/>	Return loss : .....	Multichannel <input type="checkbox"/>
Other : .....	50/125 OM3 <input type="checkbox"/> Other : .....		Other : .....
			Length (M) : .....